



MEDIUM WIRED MOTOR


Technical Specification

MEDIUM WIRED MOTOR

DM35RL/SF-10/17

Radio Tubular Motor+17Rpm

Application:



Duplex blinds



Roller blinds



Roman blinds



Technical Specification

Options	Medium Wired Motor
Power	Wired - AC 230V/50Hz
Feature	Minimal sound
Bracket	Metal
Lifting capacity	11 kgs (19 sqm)
Minimum Blind Size	650 mm
Rated Speed (RPM)	17 RPM
Rated Torque (Nm)	10
Radio Frequency (MHz)	433 [±]
Technology	RTS
Max Room Temp	-10°C ~ + 70°C
Thermal Protection Time	> 4 minutes
Maximum Limit Turn(turn)	∞
Power Required	3 pin plug
Running Time	>6
Cable length	1 mtr
Tube Diameter	45mm (Round Tube)
Suitability for wet Area	No
Motor Weight	1kg

Features

- Built-in Receiver
- Switch Direction
- Radio Lock
- Jog & Tilt
- Stall Protection
- Wind-sun-rain Sensor Compatible

Control System



1 & 15 Channel



Blindtex **UAE**

Area M6-10

SAIF Zone Sharjah – United Arab Emirates

Tel: +971 65578051

Email: sales@blindtex.com

www.blindtex.com